




BDO H<sub>2</sub>O




[A] attacco standard  
standard connection  
raccord standard  
standard Anschluss  
conexión estándar



[B] attacco speciale  
special connection  
raccord spéciale  
speziell Anschluss  
conexión especial



[B5O] attacco interasse 5 cm  
pipe centres 5 cm  
raccords 5 cm  
5 cm Achsabstand Anschluss  
conexión entre ejes: 5 cm.



P\* 122/124

A* cm	inches	B* cm	inches	L* cm	inches	art*	L*	BTU Δt 50°	watt Δt 50°
39.2	15.4	120	47.2	116	45.7	HB20000S039120B	4.4	1 642	481
39.2	15.4	140	55.1	136	53.5	HB20000S039140B	5.0	1 916	561
39.2	15.4	160	63.0	156	61.4	HB20000S039160B	5.6	2 187	641
58.4	23.0	120	47.2	116	45.7	HB20000S058120B	6.2	2 297	673
58.4	23.0	140	55.1	136	53.5	HB20000S058140B	7.0	2 681	785
58.4	23.0	160	63.0	156	61.4	HB20000S058160B	7.8	3 064	898

A\* = altezza / height / hauteur / Höhe / alto  
I\* = interasse / pipe centres / distance entre depart et retour / Achsabstand / distancia entre las conexiones  
L\* = contenuto acqua / content / volume / Inhalt / volumen

art\* = articolo / model / modèle / Artikel / artículo  
P\* = pagina / page / page / Seite / página

Kcal = Watt x 0.860  
BTU = Watt x 3.413

Watt Δt 60° = Watt Δt 50° x 1.255  
Watt Δt 40° = Watt Δt 50° x 0.758  
Watt Δt 30° = Watt Δt 50° x 0.530  
Watt Δt 20° = Watt Δt 50° x 0.320

p max = 10.0 bar

Colori/ colours / couleurs / Farbe / colores

[ BIAN ]    B standard  
                  T + 10%  
                  S + 20%

[ RAL ]        S + 20%  
                  RAL non inclusi in tabella  
                  special Ral colours  
                  couleurs Ral spéciales  
                  RAL Farbe nicht in der Tabelle inbegriffen  
                  colores RAL especiales

Ulteriori dettagli  
Further details  
Ultérieures détails  
Weitere Einzelheiten  
Otros detalles

P\* 120